

## Aluminum Single-Point Load Cell

### FEATURES

- Capacities 2–5 kg
- Aluminum construction
- Single-point 200 x 200 mm platform
- IP66 protection
- Total error better than 0.0067% of R.O.


### APPLICATIONS

- Bench scales
- Counting scales
- Grocery scales

### DESCRIPTION

Model 1006 is a very low capacity, high precision single-point load cell designed for direct mounting in low capacity scales.


This load cell is suitable for applications including postal scales, counting scales, general-purpose weighing



scales and is also suitable for a wide variety of force measurement applications, such as industrial process control or specialist medical devices.

Model 1006 offers very high performance from a very small size. It is very easy to use, and easy to apply in a wide variety of applications, where the acting center of force application is within 100 mm of the load cell vertical axis.

### OUTLINE DIMENSIONS in millimeters




## Aluminum Single-Point Load Cell

| SPECIFICATIONS                            |                                     |        |                       |
|---|-------------------------------------|--------|-----------------------|
| PARAMETER                                 | VALUE                               |        | UNIT                  |
| Accuracy class                            | Non-Approved                        | G      |                       |
| Maximum no. of intervals (n)              | 1000                                | 3000   |                       |
| Rated capacity – R.C. (E <sub>max</sub> ) | 2, 3, 5                             |        | kg                    |
| Rated output – R.O.                       | 2.0                                 |        | mV/V                  |
| Rated output tolerance                    | 0.2                                 |        | ±mV/V                 |
| Zero balance                              | 0.2                                 |        | ±mV/V                 |
| Zero return, 30 min.                      | 0.050                               | 0.0170 | ±% of applied load    |
| Total error                               | 0.0300                              | 0.0200 | ±% of rated output    |
| Temperature effect on zero                | 0.0100                              | 0.0040 | ±% of rated output/°C |
| Temperature effect on output              | 0.0030                              | 0.0010 | ±% of load/°C         |
| Eccentric loading error                   | 0.0074                              | 0.0057 | ±% of rated load/cm   |
| Temp. range, compensated                  | -10 to +40                          |        | °C                    |
| Temp. range, safe                         | -20 to +70                          |        | °C                    |
| Maximum safe central overload             | 150                                 |        | % of R.C.             |
| Ultimate central overload                 | 300                                 |        | % of R.C.             |
| Excitation, recommended                   | 10                                  |        | VDC or VAC RMS        |
| Excitation, maximum                       | 15                                  |        | VDC or VAC RMS        |
| Input impedance                           | 415±20                              |        | Ω                     |
| Output impedance                          | 350±3                               |        | Ω                     |
| Insulation resistance                     | >2000                               |        | MΩ                    |
| Cable length                              | 0.4                                 |        | m                     |
| Cable type                                | 4 wire, PVC, single floating screen |        | Standard              |
| Construction                              | Aluminum                            |        |                       |
| Environmental protection                  | IP66                                |        |                       |
| Platform size (max)                       | 200 x 200                           |        | mm                    |
| Recommended torque                        | 2 and 3 kg: 4.0    5 kg: 6.0        |        | N*m                   |

All specifications subject to change without notice.

**Wiring Schematic Diagram**  
(Unbalanced bridge configuration)



## Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay Precision Group"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify Vishay Precision Group's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

Vishay Precision Group makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, Vishay Precision Group disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on Vishay Precision Group's knowledge of typical requirements that are often placed on Vishay Precision Group products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of Vishay Precision Group.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay Precision Group products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay Precision Group for any damages arising or resulting from such use or sale. Please contact authorized Vishay Precision Group personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.