











General Purpose Strain Gages

GAGE PATTERN	GAGE SERIES See Note 1	GAGE RESISTANCE (ohms)	GAGE LENGTH	
			inches	millimeters
030TU   actual size	EA, EP, SA, SK	120, 350	0.03	0.76
	Miniature 90° tee rosette. Sections are electrically independent. Matrix size: 0.25L x 0.25W in. (6.4L x 6.4W mm)			
030TY   actual size	EA, EP, SA, SK	120, 350	0.03	0.76
	Miniature 90° tee rosette with large solder tabs. Matrix size: 0.30L x 0.15W in. (7.6L x 3.8W mm)			
030WT   actual size	WA, WK, SA, SK	120	0.03	0.76
	Miniature two-element 90° tee stacked rosette. See also 032WT pattern. Matrix size: 0.17L x 0.19W in. (4.3L x 4.8W mm)			
032WT   actual size	CEA	120	0.032	0.81
	Miniature two-element 90° stacked rosette. Exposed solder tab area is 0.07 x 0.04 in (1.8 x 1.0 mm). Maximum operating temperature +150°F (+65°C). Matrix size: 0.30L x 0.30W in. (7.6L x 7.6W mm)			
044TP   actual size	EA, SA	350	0.044	1.12
	Miniature high-resistance 90° tee rosette. Matrix size: 0.14L x 0.20W in. (3.6L x 5.1W mm)			
050TG   actual size	EA, WA, EP, SA	350	0.05	1.27
	Miniature high-resistance 90° tee rosette. Sections have a common solder tab. Matrix size: 0.34L x 0.17W in. (8.6L x 4.3W mm)			

Note 1: Products with designations and options shown in bold are not RoHS compliant.

See www.vishay.com/strain-gages for complete specifications.







General Purpose Strain Gages

GAGE PATTERN	GAGE SERIES See Note 1	GAGE RESISTANCE (ohms)	GAGE LENGTH	
			inches	millimeters
060WT   actual size	WA, WK, SA, SK	120, 350, 1000	0.06	1.52
Small two-element 90° tee stacked rosette. Matrix size: 0.24L x 0.30W in. (6.1L x 7.6W mm)				
062TZ   actual size	EA, WA, WK, SA, SK	120, 350	0.062	1.57
General-purpose 90° tee rosette. Matrix size: 0.28L x 0.26W in. (7.1L x 6.6W mm)				
100TG   actual size	EA, WA, SA	350, 1000	0.1	2.54
Small high-resistance 90° tee rosette for general-purpose use. Matrix size: 0.50L x 0.19W in. (12.7L x 4.8W mm)				
120WT   actual size	WA, WD, WK, SA, SK, SD	120, 350	0.12	3.05
Two-element 90° tee stacked rosette. Matrix size: 0.34L x 0.40W in. (8.6L x 10.2W mm)				
125TA   actual size	EA, WA, WK, SA, SK	120, 350	0.125	3.18
General-purpose two-element 90° tee rosette. Sections have a common electrical connection. See also 125TB pattern. Matrix size: 0.36L x 0.41W in. (9.1L x 10.4W mm)				
125TB   actual size	EA, EK, WA, WK, SA, SK	350, 1000	0.125	3.18
General-purpose two-element 90° tee rosette. Same geometry as 125TA but with higher resistance. Sections have common electrical connection. EK-Series gages are supplied with duplex copper dots (DD) when optional feature W or SE is not specified. Matrix size: 0.36L x 0.44W in. (9.1L x 11.2W mm)				

Note 1: Products with designations and options shown in bold are not RoHS compliant.

See www.vishay.com/strain-gages for complete specifications.



General Purpose Strain Gages

GAGE PATTERN	GAGE SERIES See Note 1	GAGE RESISTANCE (ohms)	GAGE LENGTH	
			inches	millimeters
125TF  actual size	EA, SA, SK	120, 350	0.125	3.18
General-purpose two-element 90° tee rosette with narrow pattern geometry. Sections have a common electrical connection. Matrix size: 0.59L x 0.21W in. (15.0L x 5.3W mm)				
125TQ  actual size	EA, EK, WA, WK, EP, SA, SK	350, 1000	0.125	3.18
General-purpose two-element 90° tee rosette. EK-Series gages are supplied with duplex copper dots (DD) when optional feature W or SE is not specified. Matrix size: 0.42L x 0.47W in. (10.7L x 11.9W mm)				
125VA  actual size	EA, EP, SA, SK	350, 1000	0.125	3.18
General-purpose two-element 90° tee rosette with high-resistance grid. See also 125VB pattern. Matrix size: 0.64L x 0.23W in. (16.3L x 5.8W mm)				
125VB  actual size	EA, EP, SA, SK	120, 350	0.125	3.18
General-purpose two-element 90° tee rosette. Similar to 125TF pattern except sections are electrically independent. See also 125VA pattern. Matrix size: 0.64L x 0.23W in. (16.3L x 5.8W mm)				
250TB  actual size	EA, EK, WA, WK, SA, SK	350, 1000	0.25	6.35
General-purpose two-element 90° tee rosette. EK-Series gages are supplied with duplex copper pads (DP) when optional feature W or SE is not specified. Matrix size: 0.63L x 0.81W in. (16.0L x 20.6W mm)				
250TM  actual size	EA, WA, WK, EP, SA, SK	120, 350	0.25	6.35
General-purpose two-element 90° tee rosette. Sections are electrically independent. Matrix size: 0.53L x 0.75W in. (13.5L x 19.1W mm)				

Note 1: Products with designations and options shown in bold are not RoHS compliant.

See www.vishay.com/strain-gages for complete specifications.

General Purpose Strain Gages

GAGE PATTERN	GAGE SERIES See Note 1	GAGE RESISTANCE (ohms)	GAGE LENGTH	
			inches	millimeters
<p>250WQ</p>  <p>actual size</p>	CEA	350	0.25	6.35
<p>Two-element 90° tee stacked rosette. Maximum operating temperature + 150°F (+65°C). Exposed solder tab area is 0.11 x 0.07 in (2.8 x 1.8 mm). Matrix size: 0.55L x 0.55W in. (14.0L x 14.0W mm)</p>				
<p>250WT</p>  <p>actual size</p>	WA, WD, WK, SA, SK, SD	120, 350	0.25	6.35
<p>Two-element 90° tee stacked rosette. Matrix size: 0.51L x 0.60W in. (13.0L x 15.2W mm)</p>				

Note 1: Products with designations and options shown in bold are not RoHS compliant.

See www.vishay.com/strain-gages for complete specifications.

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay Precision Group"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify Vishay Precision Group's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

Vishay Precision Group makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, Vishay Precision Group disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on Vishay Precision Group's knowledge of typical requirements that are often placed on Vishay Precision Group products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of Vishay Precision Group.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay Precision Group products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay Precision Group for any damages arising or resulting from such use or sale. Please contact authorized Vishay Precision Group personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.