






## FAE (Constantan Foil, Polyimide Carrier) Series Strain Gages

The complete range of BLH SR-4® strain gages and installation accessories are now a part of the extensive line of measurement products. And, while many similar Micro-Measurements strain gages and installation accessories are also available, our customers will continue to have the option of purchasing those BLH SR-4 products with which they are already familiar, whenever possible.

A representative listing of the most popular BLH SR-4 general-purpose strain gages are shown here. For availability of other BLH SR-4 strain gages in other patterns and series - including those for transducer applications - please contact the Customer Service Department at Micro-Measurements.

GAGE PATTERN	 <b>RoHS</b> COMPLIANT	DESIGNATION	DIMENSIONS — inches [millimeters]					MATRIX	
			RES. IN OHMS	GRID LENGTH	OVERALL LENGTH	GRID WIDTH	Length	Width	
		FAE-25-12SX	120 ± 0.2	0.250 [6.35]	0.350 [8.89]	0.125 [3.18]	0.548 [13.92]	0.250 [6.35]	
		FAE-25-35SX	350 ± 0.5	0.250 [6.35]	0.350 [8.89]	0.125 [3.18]	0.548 [13.92]	0.250 [6.35]	
		FAE-25-100SX	1000 ± 0.2	0.235 [5.97]	0.425 [10.79]	0.175 [4.44]	0.710 [18.03]	0.465 [11.81]	
		FAE-12-12SX	120 ± 0.2	0.125 [3.18]	0.180 [4.57]	0.065 [1.65]	0.354 [8.99]	0.175 [4.45]	
		FAE-12-35SX	350 ± 0.5	0.125 [3.18]	0.180 [4.57]	0.062 [1.57]	0.359 [9.12]	0.180 [4.57]	
		FAE-12-100SX	1000 ± 0.2	0.125 [3.18]	0.185 [4.70]	0.062 [1.57]	0.364 [9.25]	0.185 [4.70]	
Half-Square Grid - General Purpose									
		FAE-12S-12SX	120 ± 0.2	0.122 [3.10]	0.190 [4.38]	0.125 [3.18]	0.364 [9.25]	0.240 [6.10]	
		FAE-12S-35SX	350 ± 0.5	0.122 [3.10]	0.190 [4.38]	0.125 [3.18]	0.375 [9.53]	0.240 [6.10]	
		FAE-06S-12SX	120 ± 0.2	0.062 [1.57]	0.130 [3.30]	0.062 [1.57]	0.308 [7.82]	0.180 [4.57]	
		FAE-06S-35SX	350 ± 0.5	0.062 [1.57]	0.130 [3.30]	0.062 [1.57]	0.308 [7.82]	0.180 [4.57]	
Square Grid - High Power Dissipation									
		FAE-03W-12SX	120 ± 0.2	0.031 [0.79]	0.075 [1.90]	0.062 [1.57]	0.269 [6.83]	0.140 [3.56]	
		FAE-03W-35SX	350 ± 0.5	0.031 [0.79]	0.075 [1.90]	0.062 [1.57]	0.269 [6.83]	0.152 [3.86]	
Wide Grid - General Purpose, Low Profile									
		FAET-12A-12SX	120 ± 0.2	0.125 [3.18]	0.245 [6.22]	0.125 [3.18]	0.475 [12.07]	0.460 [11.68]	
		FAET-12A-35SX	350 ± 0.5	0.125 [3.18]	0.245 [6.22]	0.125 [3.18]	0.475 [12.07]	0.460 [11.68]	
Tee-Rosette - General Purpose									
		FAER-25B-12SX	120 ± 0.2	0.250 [6.35]	0.380 [9.65]	0.125 [3.18]	0.604 [15.34]	0.935 [23.75]	
		FAER-25B-35SX	350 ± 0.5	0.250 [6.35]	0.385 [9.78]	0.125 [3.18]	0.600 [15.24]	0.935 [23.75]	
		FAER-12B-12SX	120 ± 0.2	0.125 [3.18]	0.190 [4.77]	0.062 [1.57]	0.350 [8.89]	0.485 [12.32]	
		FAER-12B-35SX	350 ± 0.5	0.125 [3.18]	0.190 [4.77]	0.062 [1.57]	0.355 [9.02]	0.500 [12.70]	
3 Element Rosette - 45° Planar									

## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay Precision Group"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay Precision Group disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay Precision Group's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay Precision Group.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay Precision Group products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay Precision Group for any damages arising or resulting from such use or sale. Please contact authorized Vishay Precision Group personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.